::ODMA\MHODMA\IMANAGE;247158;:



PATENT APPLICATION Docket No.: 2479.2021-000 (TAN00-11)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

v 4co

08 08-01

pplicants:

John E. Hoffmann, George Rodney Nelson, Jr.,

Daniel I. Riley, Antoine J. Rouphael, James A. Proctor, Jr.

Application No.:

09/773,253

Group:

2631

Filed:

January 31, 2001

Examiner:

N/A

For:

MAXIMIZING DATA RATE BY ADJUSTING CODES

AND CODE RATES IN CDMA SYSTEM

CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as First Class Mail in an envelope addressed to Assistant Commissioner for Patents,

Washington, D.C. 20231 on 8/10/0/

Signature

Denise A. Rose

Typed or printed name of person signing certificate

TRANSMITTAL OF FORMAL DRAWINGS

Assistant Commissioner for Patents Washington, D.C., 20231

Sir:

Transmitted herewith are formal drawings, sheets [1/7-7/7], Figures 1 through 7, for filing in the subject patent application. Acceptance of the formal drawings is respectfully requested.

Respectfully submitted,

HAMILTON, BROOK, SMITH & REYNOLDS, P.C.

David J. Thibodeau, Jr.

Registration No. 31,671


Telephone (781) 861-6240

Facsimile (781) 861-9540

Lexington, MA 02421-4799

Date:

x/10/01



App No.: 09/773,253
Tip Maximizing Data Rate By Adjusting Inventors: Hoffmann, et al.

2/7




FIG. 2

App No.: 09/773,253 e: Maximizing Data Rate By Adjusti Hoffmann, et al. 3/7 80 -TCP/IP FRAME 1480 82b م 82a 🥎 SEGMENT 60 **BLOCK ENCODER 61** 83 -(2048 FOR 1/2-4096) 2048 FEC ENCODER 62 84 -4096 MOD <u>63</u> (QAM)




FIG. 3

App No.: 09/773,253

Tip Maximizing Data Rate By Adjusting Inventors: Hoffmann, et al.

4/7




FIG. 4

App No.: 09/773,253

Tip Maximizing Data Rate By Adjusting Inventors: Hoffmann, et al.

5/7

4 1331 4096	0.050	0.100	0.150	0.200	0.250	0.299	0.349	0.399	0.449	0.499	0.549	0.599	0.649	0.699
4 2048 4096	0.076	0.152	0.228	0.304	0.380	0.456	0.532	0.608	0.684	0.761	0.837	0.913	0.989	1.065
4 3249 4096	0.122	0.244	0.366	0.487	0.609	0.731	0.853	0.975	1.097	1.218	1.340	1.462	1.584	1.706
8 1331 4096	0.075	0.150	0.225	0.299	0.374	0.449	0.524	0.599	0.674	0.749	0.824	0.898	0.973	1.048
8 2048 4096	0.114	0.228	0.342	0.456	0.570	0.684	0.799	0.913	1.027	1.141	1.255	1.369	1.483	1.597
8 3249 4096	0 183	0.366	0.548	0.731	0.914	1.097	1.279	1.462	1.645	1.828	2.010	2.193	2.376	2.559
16 1331 4096	0.100	0.200	0.299	0.399	0.499	0.599	0.699	0.799	0.898	0.998	1.098	1.198	1.298	1.398
16 2048 4096	0 152	0.304	0.456	0.608	0.761	0.913	1.065	1.217	1.369	1.521	1.673	1.825	1.977	2.129
16 3249 4096	0 244	0.487	0.731	0.975	1.218	1.462	1.706	1.949	2.193	2.437	2.680	2.924	3.168	3.411
64 1331 4096	0.150	0.299	0.449	0.599	0.749	0.898	1.048	1.198	1.348	1.497	1.647	1.797	1.947	2.096
64 2048 4096	0.228	0.456	0.684	0.913	1.141	1.369	1.597	1.825	2.053	2.282	2.510	2.738	2.966	3.194
64 3249 4096	998 0	0.731	1.097	1.462	1.828	2.193	2.559	2.924	3.290	3.655	4.021	4.386	4.752	5.117
MOD INFO SIZE	CHANNEL	14	9	80	10	12	14	76	18	20	22	24	26	58

FIG. 5

App No.: 09/773,253

Titl Maximizing Data Rate By Adjusting Inventors: Hoffmann, et al.



4 684 2048	0.064	0.103	0.154	0.205	0.257	0.308	0.359	0.410	0.462	0.513	0.564	0.616	0.667	0.718
4 858 2048	7900	0.129	0.193	0.257	0.322	0.386	0.450	0.515	0.579	0.644	0.708	0.772	0.837	0.901
4 1482 2048	7	0.222	0.333	0.445	0.556	0.667	0.778	0.889	1.000	1.112	1.223	1.334	1.445	1.556
8 684 2048	2200	0.154	0.231	0.308	0.385	0.462	0.539	0.616	0.693	0.770	0.846	0.923	1.000	1.077
8 858 2048	7000	0.193	0.290	0.386	0.483	0.579	9.676	0.772	0.869	0.965	1.062	1.158	1.255	1.351
8 1482 2048	0.167	0.333	0.500	0.667	0.834	1.000	1.167	1.334	1.501	1.667	1.834	2.001	2.167	2.334
16 684 2048	0.103	0.205	0.308	0.410	0.513	0.616	0.718	0.821	0.923	1.026	1.129	1.231	1.334	1.436
16 858 2048	0.120	0.257	0.386	0.515	0.644	0.772	0.901	1.030	1.158	1.287	1.416	1.544	1.673	1.802
16 1482 2048	6660	0.445	0.667	0.889	1.112	1.334	1.556	1.778	2.001	2.223	2.445	2.668	2.890	3.112
64 684 2048	0.157	0.308	0.462	0.616	0.770	0.923	1.077	1.231	1.385	1.539	1.693	1.847	2.001	2.155
64 858 2048	0.103	0.386	0.579	0.772	0.965	1.158	1.351	1.544	1.737	1.931			2.510	2.703
64 1482 2048	888 U	0.667	1.000	1.334	1.667	2.001	2.334	2.668	3.001	3.335	3.668	4.001	4.335	4.668
MOD TPC RATE SIZE	CODES	14	9	80	10	12	14	16	18	20	22	24	26	58

App No.: 09/773,253

The: Maximizing Data Rate By Adjusting.

Inventors: Hoffmann, et al.



7/7

4 363 1024	0.054	0.109 0.163	0.218	0.272	0.327	0.381	0.436	0.490	0.545	0.599	0.653	0.708	0.762
4 676 1024	0.101	0.203	0.406	0.507	0.608	0.710	0.811	0.913	1.014	1.115	1.217	1.318	1.420
8 363 1024	0.082	0.163 0.245	0.327	0.408	0.490	0.572	0.653	0.735	0.817	0.898	0.980	1.062	1.143
8 676 1024	0.152	0.304	0.608	0.761	0.913	1.065	1.217	1.369	1.521	1.673	1.825	1.977	2.129
16 363 1024	0.109	0.218	0.436	0.545	0.653	0.762	0.871	0.980	1.089	1.198	1.307	1.416	1.525
16 676 1024	0.203	0.406	0.811	1.014	1.217	1.420	1.622	1.825	2.028	2.231	2.434	2.636	2.839
64 363 1024	0.163	0.327	0.653	0.817	0.980	1.143	1.307	1.470	1.634	1.797	1.960	2.124	2.287
64 676 1024	0.304	0.608 0.913	1.217	1.521	1.825	2.129	2.434	2.738	3.042	3.346	3.650	3.955	4.259
MOD INFO SIZE	CODES	4 0	ω	10	12	14	16	18	20	22	24	26	28